

D580

Samhoo

D580

Digital Two way radio



- DMR Tier2&Tier1, Analogue FM
- UHF 400–520M and VHF 136–174M
- Clearer&Louder Audio with AI-based
- Longer range with higher sensitivity
- Longer battery life with 2000mAh
- 80h+ long standby time
- Safer side flash light
- Rugged & Reliable IP56/66/67



Safety flashing light

Frequency range*:
V(136-174MHz)
U1(400-470MHz)
U2(350-400MHz)
U4(450-520MHz)



CE FC RoHS MIL-STD

General

Communication protocols & standards	DMR Tier1 & Tier2
Working Mode	Analogue
Frequency Bands	136-174MHz,350-400MHz,400-470MHz,450-520MHz
Channel Capacity	256 Channel,16 Zone
Channel Spacing	12.5KHz/20KHz/25KHz
Operating Voltage	7.4V
Battery Volume	2000mAh(Lithium battery)
Working Time _(standard battery) (5-5-90 duty cycle, high TX power)	≥28h
Dimensions _(standard battery, not including antenna)	117.1*54.5*31.5(mm)(H*W*D)
Weight _(standard battery, including antenna)	270±5g
Frequency Stability	±0.5ppm
Digital Voice Vocoder	AMBE++

Transmitter

RF Power Output	UHF High/Low power: 4W/1W VHF High/Low power: 5W/1W
FM Modulation	11K0F3E@12.5KHz;14K0F3E@20KHz;16K0F3E@25KHz
4FSK Digital Modulation	12.5KHz Data:7K60FXD 12.5KHz Data&Voice:7K60FXW
Conducted / Radiated Emission	-36dBm < 1GHz;-30dBm > 1GHz
Modulation Limiting	±2.5KHz@12.5KHz;±4.0KHz@20KHz;±5.0KHz@25KHz
FM Noise	40dB@12.5KHz;43dB@20KHz;45dB@25KHz
Adjacent Channel Power	60dB@12.5KHz
Audio Response	+1~-3dB
Audio Distortion	≤3%

Receiver

Sensitivity	Digital	0.14μV(BER5%)
Sensitivity	Analog	0.14μV(12dB SINAD)
Adjacent Selectivity	≥60dB@12.5KHz	
Hum and Noise	40dB@12.5KHz;43dB@20KHz;45dB@25KHz;	
Rated Audio Power Output	0.5W	
Rated Audio Distortion	≤3%	
Audio Response	+1~-3dB	
Conducted Spurious Emission	< -57dBm	

Environmental Specifications

Operation temperature	-20℃~+60℃
Storage temperature	-40℃~+85℃
ESD	IEC 61000-4-2(level 4);±8KV(contact);±15KV(air)
Environment Test Standard	MIL-STD
Dust and water ingress protection	IP56/66/67

Remark: The above specifications comply with standard tests accordingly, and due to continuous technical development, they are subject to changes without prior notice.

Standard:



Standard Battery



Antenna



Power adapter



Desktop charger



Belt Clip



Strap

Optional:



D-Earset



Programming Cable



Desk Charger Power adapter



Six-Slot Desk Charger



Hand microphone



Transparent Acoustic Tube Earset

Your Local Dealer



ISO certification:

ISO9001:2015

ISO14001:2015

ISO45001:2018



www.samhoo.com.cn
Learn more details



RECYCLABLE

